



From Serial Number 45412341

FOREWORD

This document is the property of Auger Torque and the information contained herein is confidential to the company. The contents of the document must not be reproduced or disclosed wholly or in part, or used for purposes other than that for which it has been supplied, without the prior written permission of Auger Torque.

This manual has been written in the standard United Kingdom English Language. Auger Torque accepts no responsibility or liability for customer or any other third party translations of this manual into other languages, or for any incidents arising from such translation.

Auger Torque operates a policy of continuous product improvement, and actively encourages feedback on user manuals. If you wish to comment on the contents of this manual please send your comments using the feedback form provided. Please copy and complete the hard copy form on the back page of this manual.

SAFETY

Auger Torque Earth Drill Units have been designed for use with specific Auger Torque mounting frames, Augers, Auger extensions and Auger wear parts. Provided these are used and maintained correctly, they will provide a safe and reliable method of boring holes in the earth.

Use of this product following unauthorised modifications or repairs, use by untrained personnel, by implementing unsafe systems of work, by making modifications to product supplied or through operation in any manner not intended by Auger Torque could result in death, serious injury, damage to property or the product itself, and will invalidate any product validation or warranty. Auger Torque accepts no responsibility whatsoever for such modifications, repair or use.

WARRANTY

Auger Torque is not responsible for nor will accept any charges for work carried out by any unauthorised repairers. Charges, including those for spare parts, will not be accepted unless they have been authorised in writing by Auger Torque.

Any goods returned to Auger Torque by the customer, under warranty or for repair, must be freight paid unless authorised in writing by Auger Torque.

For full terms and condition see:-

www.augertorque.com/about-us/warranties.html

CONTACT DETAILS

Please contact your local dealer / distributor via our website

www.augertorque.com/dealer-locator.html

Auger Torque Europe Ltd. Tel:+44 (0) 1451 861 652

Auger Torque Australia Pty Ltd. Tel: +61 (0) 7 3274 2077

Attachment Torque MFG(China) Co.,Ltd Tel: +86 (0) 574 88488181

Auger Torque Products Kinshofer USA Tel: +1 716 731 4333



From Serial Number 45412341

THE MACHINERY DIRECTIVE

The Machinery Directive 2006/42/EC (formerly 98/37/EEC) provides the harmonisation of the essential health and safety requirements for machinery, through a combination of mandatory health and safety requirements and voluntary harmonised standards. Such directives apply only to products that are intended to be placed on or put into service in the market for the first time.

The manufacturer or the authorised representative must draw up a 'Declaration of Conformity'.

Declaration of Conformity

Where Earth Drill Units are supplied in conjunction with Auger Torque manufactured mounting frames and Augers to form an Earth Drill Assembly, Auger Torque have control over the suitability of the parts supplied. To show this and meet with the lawful requirements of the Machinery Directive a Declaration of Conformity is issued and a CE mark is applied to the assembly.

SYMBOLS AND ABBREVIATIONS

The symbols that follow are used within this publication



From Serial Number 45412341

ILLUSTRATED PARTS LIST.

- A The Illustrated Parts List helps the supply procedure and the identification of replacement component parts.
- B The Detailed Parts List is divided into seven columns:
 - The first column gives the item number of each detailed part contained in the illustration. An item number prefixed by a (-), shows that the item is not illustrated.
 - The second column gives the part number by which the item is identified.
 - The third column, gives the description of the component. The description will be preceded by one or more dots (•).
 - The fourth column gives the quantity of each item in the complete assembly.
 - The fifth column shows the torque tightening required for the item.
 - The sixth column shows the thread treatment required for the item.
 - The seventh column makes reference to any additional information required for the part or assembly.
- C Only those items with full dots (●) can be ordered as spares. Items with empty dots (eg ●o) are shown only for clarity of assembly and cannot be ordered as spares.


- D When ordering spare parts please quote the serial number of the Earth Drill, which can be identified from the serial number plate on the top of the unit.
- NOTE: Auger Torque will not accept any liability for incorrect parts that may be supplied because an incorrect serial number has been quoted.

The abbreviations that follow are used within this publication

AR As Required BSP **British Standard Pipe Thread Cubic Centimeters** СС Kq Kilogrammes L. Litres Litres Per Minute LPM Millimeters Mm Newton Meters Nm Unified Coarse Thread UNC GPM Gallons Per Minute G Gallons lbs Pounds ft-lbs Foot Pounds










ITEM	PART NO.	DESCRIPTION	QTY	TORQUE LOAD	THREAD TREATMENT	NOTES
10	23-4905	HOOD ASSAY - SERIES 4.5	1			
20	99-9139-045	 FIXING - M14 x 45 SOCKET CAP SCREW (12.9 Grade) 	4	142 - 215 ft-lbs	LOCTITE 243	
30	99-9233	 FIXING - M14 NORD WASHER 	4	142 21010 005		
40	25-4004	MOTOR - EATON 6K 310cc - 17T SHAFT	1			
50	25-4006	SEAL KIT - MOTOR - REAR	1			
	25-4005	SEAL KIT - MOTOR - SHAFT	1			
60	21-4986-S	 DRIVE SUB-ASSEMBLY Series 4.5 -4 & 6K - 75mm SQUARE 	1			
70	30-0002-KIT	• PIN - AUGER C/W LINCH PIN	1			
80	30-0002	● ○ PIN	1			
90	99-99020	●○ LINCH PIN - n9.5 (To fit over UPTO Ø36mm SHAFTS)	1			
100	99-9135-065-Y	• FIXING - M12 x 65 SOCKET CAP SCREW (12.9 Grade) YELL.PASS.	16	89 - 99 ft-lbs	LOCTITE 243	
110	99-9231	FIXING - M12 NORD WASHER	16			
120	23-4027	SIGHT GLASS GUARD - SERIES 4.5 DRIVES	1			
130	99-9153	FIXING - M8 PLAIN WASHER	4			
140	99-9123-20	• FIXING - M08 x 020mm Setscrew (8.8 Grade)	4			
150	99-9185	FIXING - M12 METRIC NYLOC NUT (8 Grade)	2	Refer to Operators Manual		
160	23-4016	• PIN - 45mm x 210 LONG - SERIES 4	1			
170	99-9115-090	• FIXING - M12 x 090mm - Bolt (8.8 Grade)	2	Refer to Operators Manual		
						Ref. 18500S-0001-1








ITEM	PART NO.	DESCRIPTION	QTY	TORQUE LOAD	THREAD TREATMENT	NOTES
10	21-4986-S	DRIVE SUB-ASSEMBLY Series 4.5 - 4 & 6K - 75mm SQUARE	1			
20	99-1537-V	• O'RING - 134 ID x 3.0 (Motor seal)	1			See Seal Kit
30	99-9135-060	 FIXING - M12 x 60 SOCKET CAP SCREW (12.9 Grade) 	8	89 - 99 ft-lbs	LOCTITE 243	See Sederat
40	21-5071	 1/2" BSP MAGNETIC PRESSURE PLUG 	1		2001112 240	
50	21-5015	TOP INPUT HOUSING - 6K	1			
60	99-1533-V	$\bullet \circ$ O'RING - 199 ID x 3.0 (Series 4 RING)	3			See Seal Kit
70	21-5070	• SIGHT GLASS	1			
80	99-7009	•• BONDED SEAL - 2.0 INCH	1			See Seal Kit
90	21-5093	• PLUG - M20 x 1.5 x 15mm LONG	1			
100	21-5094	$\bullet \circ$ SEAL - BONDED RUBBER - M20	1			See Seal Kit
110	99-7102	• 1/4" BSPT PLUG - ALLEN DRIVE	1			
120	21-5078	EXTENDED HOUSING - SERIES 5	1			
130	99-9135-080	• FIXING - M12 x 80 SOCKET CAP SCREW (12.9 Grade)	8	89 - 99 ft-lbs	LOCTITE 243	
140	99-9231	FIXING -M12 NORD WASHER	8			
150	21-5137	• RING GEAR - 76T 2.5/2.0 MOD - 34mm	1			
160	21-4101	• BOTTOM INPUT HOUSING - 17 000-25 000MAX	1			
170	99-1556-V	• 0 'RING - 238 ID x 3.0 (Series 4.5 RING)	2			See Seal Kit
180	21-4104	• RING GEAR - 62T 3.5/3.0 MOD - 36mm	1			
190	99-9135-110	• FIXING - M12 x 110 SOCKET CAP SCREW (12.9 Grade)	12	89 - 99 ft-lbs	LOCTITE 243	
200	21-4112	• SUN GEAR - 17T - 2.5/2.0 MOD - 4 & 6K MOTORS	1			
210	21-4051	WEAR WASHER - SERIES 4 & 4.5	1			
220	99-1606	CIRCLIP - EXTERNAL HD DI 471 SIZE-28	2			
230	21-5121-4.5	WASHER - SERIES 4/4.5 CARRIER RETAINER	1			
240	21-4915	GEAR CARRIER ASSEMBLY - SERIES 4.5 - 3.5/3.0 MOD	1			
250	99-1606	CIRCLIP - EXTERNAL HD DI 471 SIZE-28	3			
260	21-4115	PLATE - RETIANER - PLANET POST	1			
270	21-4918	PLANET GEAR ASSEMBLY - 4.5 SERIES INPUT STAGE	3		LOCTITE 277	
280	21-4111	• CARRIER - 22T 3.5/3.0 MOD SERIES 4.5	1			
290	21-4110	WASHER - HARDENED PLANET CARRIER SERIES 4.5	1			
300	21-4917	• SHAFT ASSEMBLY - 75mm SQUARE - Series 4.5	1			
310	99-1606	CIRCLIP - EXTERNAL HD DI 471 SIZE-28	8			
320	21-4108	• PLATE - GEAR RETIANER - 17 000 - 25 000MAX	1			
						Ref. 12500S-0002-1








ITEM	PART NO.	DESCRIPTION	QTY	TORQUE LOAD	THREAD TREATMENT	NOTES
330	21-4109	CENTRAL POST - EXTENDED	1	111 ft-lbs		
340	21-4916	 PLANET GEAR ASSEMBLY - 4.5 SERIES OUTPUT STAGE 	4		LOCTITE 277	
350	21-4100	SHAFT - OUTPUT (4 Post) - 75mm SQUARE	1			
360	21-4905	OUTPUT SUB-ASSEMBLY - SERIES 4.5 DRIVES	1			
370	99-1111	 BEARING - TAPER 120 ID x 180 OD x 38 THK 	2		LOCTITE 7471, 641	
380	21-5071	 1/2" BSP MAGNETIC PRESSURE PLUG 	2			
390	21-4102	OUTPUT HOUSING - SERIES 4.5	1			
400	99-1519	• OIL LIP SEAL (160x190x15)	1		LOCTITE 7471, 515	See Seal Kit
410	21-4117	 LOCKING NUT - 4.5 SERIES 	1	332 ft-lbs	LOCTITE 209125	
420	21-4116	 PLATE - SEAL - SERIES 4.5 (16 000 - 25 000) 	1			
430	99-9142-020	 FIXING - M6 x 20mm LONG CNSK SET SCREW (10.9 Grade) 	8	10.6 - 12 ft-lbs	LOCTITE 243	
440	99-9214-012	 SOCKET SET SCREW - M10 x 12 DOG POINT (14.9 Grade) 	2		LOCTITE 243	
450	SK-21-495	• SEAL KIT - GEARBOX - SERIES 4.5 - Comprising of items 20,60,80,100,170 & 400	1			
460	99-8101	GEAR OIL - AGMA 6EP - MINERAL (1 Litre Bottle)	7			14.26 US pints required
		All units are supplied with AGMA 6EP viscosity oil, except where the				
		unit is to be or stored in extreme temperatures.				
	99-8104	• GEAR OIL - AGMA 4EP - MINERAL When using or storing the units below -15°C				
	99-8106	• GEAR OIL - AGMA 7EP- MINERAL When using or storing the units above 35°C				
						Ref. 12500S-0002-1
						nei. 123003-0002-1



From Serial Number 45412341

Ref. 170-0001-1






ITEM	PART NO.	DESCRIPTION	QTY	TORQUE LOAD	THREAD TREATMENT	NOTES
10	TOOL - 1917	PLANET POST TOOLING	1			
20	TOOL - 1910	PLANET POST TOOLING	1			
30	TOOL - 1121	RETAINING PLATE BUSH	4			
40	TOOL - 1118	RETAINING PLATE	1			
50	TOOL - 1916	TOOL - LOCK NUT	1			
60	TOOL - 1139	TOOL - SEAL PRESS SERIES 4.5	1			
70	TOOL - 1123	BEARING PRESS	1			
80	99-8217	LOCTITE - 7471 ACTIVATOR	1			
	99-8205	LOCTITE - 243 THREADLOCKER	1			
	99-8202	LOCTITE - 515 FLANGE SEALANT	1			
	99-8206	LOCTITE - 277 THREADLOCKER	1			
	99-8214	LOCTITE - 641 BEARING RETAINER	1			
	99-8210	 LOCTITE - 209125 (BLUEMAX) 	1			
	99-8218	LOCTITE - 577 THREAD SEALANT	1			
						Ref. 170-0001-1



From Serial Number 45412341

Ref. 18500-0001-1





ITEM	PART NO.	DESCRIPTION	QTY	TORQUE LOAD	THREAD TREATMENT	NOTES
10	99-8002	PAINT - AUGER TORQUE BLUE 0.5L	1			
20	99-5325	LABEL - ATUSA PRE-RUN CHECKS	1			
30	99-5307	LABEL - NOTICE	1			
40	99-5305	LABEL - DANGER - USA	1			
50	99-5306	LABEL - WARNING - USA	1			
60	99-5061	LABEL - SIGHT GLASS COVER	1			
70	99-5062	LABEL - SIGHT GLASS	1			
80	99-5436	LABEL - OUTPUT LABEL - TRANSPARENT BACKGROUND	1			
90	99-5064	LABEL - CHECK BEFORE OPERATION	1			
100	99-5280	LABEL - ATUSA - 18500-45 - IDENTITY LABEL	1			
110	99-95-200001	OPERATOR'S MANUAL - ENGLISH	1			
	99-95-200002	OPERATOR'S MANUAL - FRENCH	1			
	99-95-200003	OPERATOR'S MANUAL - FINNISH	1			
	99-95-200004	OPERATOR'S MANUAL - RUSSIAN	1			
	99-95-200005	OPERATOR'S MANUAL - GERMAN	1			
	99-95-200006	OPERATOR'S MANUAL - POLISH	1			
	99-95-200007	OPERATOR'S MANUAL - SPANISH	1			
	99-95-200008	OPERATOR'S MANUAL - DUTCH	1			
	99-95-200009	OPERATOR'S MANUAL - ARABIC	1			
	99-95-200010	OPERATOR'S MANUAL - DANISH	1			
						Dof 19500 0001 1
						Ref. 18500-0001-1



Auger Torque Publication Feedback Form						
Please copy this form and when complete return to the address below						
	Your Contact Details	Please enter your feedback in the field below :-				
Name :-						
Address :-						
Telephone :-						
Email :-						
Publication Number						
Publication Title						
Issue/Rev Number						
	Auger Torqu Kinsho 6420 Indu Suit Sanborn, US Phone (+1) 7 Fax (+1) 71	fer USA con Drive re G NY, 14132 5A 716 731 4333				
	Fax (+1) 71 Email sales@aug					