



MB-G450 S4



ACCESSORIES

- MULTI-PURPOSE BLADE KIT
- CLAM SHELL KIT
- SERRATED SIDE PLATE KIT
- RUBBER PROTECTION KIT
- ELECTRICAL KIT FOR 2 LINE FUNCTIONALITY
- 24 MONTH WARRANTY

SPECIFICATIONS

RECOMMENDED EXCAVATOR	≥ 3 ≤ 6 ton
WEIGHT	288 kg / 0,288 ton
CAPACITY (CLAWS CLOSED)	0,10 m ³
ROTATION	360° Gradi
OIL PRESSURE (ROTATION)	> 150 bar
OIL FLOW RATE (ROTATION)	10 l/min.
OIL PRESSURE (OPENING/CLOSING)	0 - 250 bar
OIL FLOW RATE (OPENING/CLOSING)	40 l/min.

APPLICATION AREAS



DEMOLITIONS



ROAD WORKS



TUNNELS AND
ENCLOSED SPACES



PIPELINES



URBAN
CONSTRUCTION
SITES



MAINTAINING
LANDSCAPE AND
AGRICULTURAL AREAS



FOREST
MAINTENANCE

The data provided above is not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.

Rev. 2022/11



MBCRUSHER.COM