

FORESTRY MULCHERS FOR SKID STEERS

UML/SSL/BL

Forestry mulcher with Bite Limiter rotor system.

Robust and compact, the UML/SSL/BL is renowned for its ergonomic design that guarantees excellent visibility for the operator during various situations. The VT version with automatic variable displacement

hydraulic motor increases productivity by up to 50% and simultaneously reduces fuel consumption.



Sonic System



75-120 hp



Ø 8 in max



Rotor Bite Limiter



Sonic System is a new automatic intelligent system that manages the hydraulic transmission. It makes the mulching machine to perform at the maximum capacity in all conditions (UML/SSL/BL/SONIC)



Reinforced frames
Provides extra protection from the power of the carrier

STANDARD EQUIPMENT

| | |
|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| 110/60cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/BL/VT) | 110cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/BL/SONIC) |
| Adjustable skids | Working pressure control gauge |
| Safety and anticavitation valve | Guard frame |
| Enclosed / anti dust machine body | Dual row protection chains |
| Motor enclosed in the frame | Welded counterblades |
| Belt transmission (Poly Chain®) | Rotor Bite Limiter |
| Hydraulic hoses | Sonic System (UML/SSL/BL/SONIC) |
| Rear deflector | Adaptor wiring |

OPTIONS


| | |
|----------------------------------------------------|-----------------------------------------------|
| Customized setting hydraulic motor (UML/SSL/BL/VT) | Universal cabin roof hydraulic oil cooler kit |
| Oil cooler kit | |

Case drain required

| MODEL | UML/SSL/BL/VT-150 | UML/SSL/BL/VT-175 | UML/SSL/BL/SONIC-150 | UML/SSL/BL/SONIC-175 |
|------------------------------------|-------------------|-------------------|----------------------|----------------------|
| Power (hp) | 75-120 | 75-120 | 75-120 | 75-120 |
| Flow rate (gal/min) | 32-53 | 32-53 | 32-53 | 32-53 |
| Pressure (PSI) | 2900-5080 | 2900-5080 | 2900-5080 | 2900-5080 |
| Working width (in) | 62 | 72 | 62 | 72 |
| Total width (in) | 74 | 83 | 74 | 83 |
| Weight (lbs) | 2866 | 3086 | 2866 | 3086 |
| Rotor diameter (in) | 17.3 | 17.3 | 17.3 | 17.3 |
| Max shredding diameter (in) | 8 | 8 | 8 | 8 |
| No. blades type BL + C/3/SS | 24+2 | 30+2 | 24+2 | 30+2 |

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Customized setting hydraulic motor

ROTOR TYPE BL



BLADE BL (option)



TOOTH C/3/SS (side scraper)